



DESCRIPTIONS OF PRODUCT COVERED: CAMPBELL FITTINGS NSF-61|

Trade Designation USC, CNC	Water Use Temperature, (°C)	Size Range (in.)
*"Coupling Style HCS, HCLS"	23	0.75-12
*"Coupling Style HCPS, HCLPS"	23	0.75-12
"Coupling Style HCSS, HCLSS"	23	0.75-12
*"Coupling Style HCB"	23	0.75-4
"Coupling Style CS, XCS, RCS"	23	0.5-6
"Coupling Style CSS, XCSS, RCSS"	23	0.75-6
"Coupling Style CB, XCB, RCB"	23	0.5-4
*"Adapter Style HAS, HALS"	23	0.75-12
*"Adapter Style HAGS, HAGLS"	23	0.75-12
*"Adapter Style HAPS, HALPS"	23	0.75-12
*"Adapter Style HAGPS, HALGPS"	23	0.75-12
*"Adapter Style HASS, HALSS"	23	0.75-12
*" Adapter Style HAGSS, HAGLSS"	23	0.75-12
*" Adapter Style HAB, HALB"	23	0.75-4
*"Adapter Style HRS, HRGS, HRGLS"	23	0.75-6
*" Adapter Style HES, HEGS"	23	0.75-6
*"Adapter Style HRPS, HRGPS"	23	0.75-6
*"Adapter Style HEPS, HEGPS"	23	0.75-6
*"Adapter Style HRSS, HRGSS"	23	0.75-6
"Adapter Style HESS, HEGSS"	23	0.75-6
*"Adapter Style HRB, HEB"	23	0.75-4
"Adapter Style CJMS"	23	0.75-6
"Adapter Style MAS, XS, FAS"	23	0.5-6
"Adapter Style MASS, XSS"	23	0.5-6
"Adapter Style MAB, XB, FAB"	23	0.5-4
"Adapter Style RAS, SAS"	23	0.5-6
"Adapter Style RASS, SASS"	23	0.5-6
"Adapter Style RAB, SAB"	23	0.5-4
"Adapter Style ZAS, ZBS"	23	1-1.25
"Adapter Style ZAB, ZBB"	23	1-1.25
"Venturi Style VMAS, VFAS, XVS"	23	0.75-2
"Venturi Style VMAB, VFAB, XVB"	23	0.75-2
"Ell Style WLS"	23	0.75-1.5
"Ell Style WLB"	23	0.75-1.5
"Leg Style LEG"	23	1
"Nipple Style NS"	23	0.5-6
"Nipple Style NPS"	23	0.5-6
"Nipple Style NSS"	23	0.5-6
"Nipple Style NB"	23	0.5-6